

# Ultrasonic measurement Time-of-Flight Prosonic FMU30

Cost effective all-round instrument for level applications in liquids and bulk solids



from **A\$827.00**

Price as of 23.04.2021

More information and current pricing:

[www.au.endress.com/FMU30](http://www.au.endress.com/FMU30)

## Benefits:

- Quick and simple commissioning via menu-guided onsite operation with four-line plain text display, 7 languages selectable
- Envelope curves on the on-site display for simple diagnosis
- Linearization function (up to 32 points) for conversion of the measured value into any unit of length, volume or flow rate
- Non-contact measurement method minimizes service requirements
- Installation possible from thread G 1½ or 1½ NPT upwards
- Integrated temperature sensor for automatic correction of the temperature dependent sound velocity

## Specs at a glance

- **Accuracy** +/- 3 mm or +/- 0.2 % of set measuring range
- **Process temperature** -20 °C ... 60 °C (-4 °F ... 140 °F)
- **Process pressure absolute / max. overpressure limit** 0.7 bar ... 3 bar abs (10 psi ... 44 psi)
- **Max. measurement distance** Sensor 1-1/2": 2 m (6.6 ft) Sensor 2": 3.5 m (11 ft)
- **Main wetted parts** PP/EPDM

**Field of application:** The range of applications extends from monitoring levels in sewage treatment plants and process water tanks to applications for loading, storage and buffer tanks. FMU30 ultrasonic sensor offers proven software algorithms and all warning and alarm messages are shown on the four-line plain text display and guarantee fast remedy of problems. The envelope curve can also be shown on the display. As the

analysis results are displayed directly on-site, this ensures quick and accurate error diagnostics.

## Features and specifications

### Continuous / Solids

**Measuring principle**

Ultrasonic

**Characteristic / Application**

Compact ultrasonic transmitter

**Supply / Communication**

2-wire

**Accuracy**

+/- 3 mm or +/- 0.2 % of set measuring range

**Ambient temperature**

-20 °C ... 60 °C

(-4 °F ... 140 °F)

**Process temperature**

-20 °C ... 60 °C

(-4 °F ... 140 °F)

**Process pressure absolute / max. overpressure limit**

0.7 bar ... 3 bar abs

(10 psi ... 44 psi)

**Main wetted parts**

PP/EPDM

---

**Continuous / Solids****Process connection**

G / NPT 1 1/2"

G / NPT 2"

---

**Blocking distance**

Sensor 1 1/2": 0.25 m

Sensor 2": 0.35 m

---

**Max. measurement distance**

Sensor 1-1/2": 2 m (6.6 ft)

Sensor 2": 3.5 m (11 ft)

---

**Communication**

4...20 mA

---

**Certificates / Approvals**

ATEX, CSA C/US, IEC Ex, NEPSI

---

**Options**

Accessory Enclosed:

UNI flange 2" ... 4"

---

**Application limits**

Take notice of range diagram

---

**Point Level / Solids****Measuring principle**

Ultrasonic Limit

---

**Characteristic / Application**

Compact ultrasonic transmitter

---

**Supply / Communication**

2-wire

---

**Point Level / Solids****Ambient temperature**

-20 °C...+60 °C,

(-4 °F...+140 °F)

---

**Process temperature**

-20 °C...+60 °C,

(-4 °F...+140 °F)

---

**Process pressure absolute / max. overpressure  
limit**

0.7 bar...3 bar abs,

(10 psi ...44 psi)

---

**Main wetted parts**PP/ EPDM

---

**Process connection**

G / NPT 1 1/2",

G / NPT 2"

---

**Blocking distance**

Sensor 1 1/2": 0.25 m,

Sensor 2": 0.35 m

---

**Communication**4...20 mA

---

**Certificates / Approvals**ATEX, CSA C/US, IEC Ex, NEPSI

---

**Options**

Accessory Enclosed:

UNI flange 2"...4"

---

---

**Point Level / Solids**

---

**Application limits**

Take notice of range diagramm

---

**Point Level / Liquids**

---

**Measuring principle**

Ultrasonic Limit

---

**Characteristic / Application**

Compact ultrasonic transmitter

---

**Supply / Communication**

2-wire

---

**Ambient temperature**

-20 °C...+60 °C

(-4 °F...+140 °F)

---

**Process temperature**

-20 °C...+60 °C

(-4 °F...+140 °F)

---

**Process pressure absolute / max. overpressure limit**

0.7 bar...3 bar abs

(10 psi ...44 psi)

---

**Main wetted parts**

PP/EPDM

---

**Process connection**

G / NPT 1 1/2"

G / NPT 2"

---

---

**Point Level / Liquids****Blocking distance**

Sensor 1 1/2": 0.25 m,

Sensor 2": 0.35 m

---

**Communication**

4...20 mA

---

**Certificates / Approvals**

ATEX, CSA C/US, IEC Ex, NEPSI

---

**Options**

Accessory Enclosed:

UNI flange 2"... 4"

---

**Application limits**

Take notice of range diagram

---

**Continuous / Liquids****Measuring principle**

Ultrasonic

---

**Characteristic / Application**

Compact ultrasonic transmitter

---

**Supply / Communication**

2-wire

---

**Accuracy**

+/- 3 mm or +/- 0,2 % of set measuring range

---

**Ambient temperature**

-20 °C ... 60 °C

(-4 °F ... 140 °F)

---

**Continuous / Liquids****Process temperature**

-20 °C ... 60 °C

(- 4°F ... 140 °F)

---

**Process pressure absolute / max. overpressure limit**

0.7 bar ... 3 bar abs

(10 psi ... 44 psi)

---

**Main wetted parts**

PP/EPDM

---

**Process connection**

G / NPT 1 1/2"

G / NPT 2"

---

**Blocking distance**

1 1/2": 0.25 m (0.8 ft)

2": 0.35 m (1.15 ft)

---

**Application**

Application

---

**Max. measurement distance**

Max. measurement distance

---

**Communication**

4...20 mA

---

**Certificates / Approvals**

ATEX, CSA C/US, IEC Ex, NEPSI

---

**Options**

Accessory Enclosed:

UNI flange 2" ... 4"

## Continuous / Liquids

---

### Application limits

Application limits

---

More information [www.au.endress.com/FMU30](http://www.au.endress.com/FMU30)