

# Flowfit W COA260



## Benefícios:

- Easy plate or wall mounting using clip holder
- Fast availability: Automatic de-aeration thanks to bottom inlet/top outlet design.
- Fast sensor response time thanks to low inner volume
- Minimum maintenance effort
- Easy removal of the sensor for calibration in air
- All medium contacting parts of stainless steel 1.4435 (AISI 316 L)

## Especificações resumidas

- **Process temperature** max. 50°C (max.122°F)
- **Process pressure** max. 10bar (max.145psi)

Mais informações e preço atual:

[www.br.endress.com/COA260](http://www.br.endress.com/COA260)

**Campo de aplicação:** The flow assembly Flowfit W COA260 is a plate or wall mounting assembly for the trace determination of dissolved oxygen.

## Características e especificações

### Oxygen

#### Measuring principle

Amperometric oxygen measurement

#### Application

Power plant, process

#### Characteristic

Flow through holder for the oxygen sensor COS71.

#### Design

Flow through holder to be mounted on thw wall or on a plate with input below and horizontal output.

#### Material

Holder : stainless steel 1.4571Sealing : PTFE flat sealing

Oxygen

---

**Process temperature**

max. 50°C  
(max.122°F)

---

**Process pressure**

max. 10bar  
(max.145psi)

---

Mais informações [www.br.endress.com/COA260](http://www.br.endress.com/COA260)