

# Thermophant T TTR31

## Temperature switch

Compact and cost-saving for safe monitoring of process temperatures



### Benefits:

- Integrated switching electronics for decentral and economic process monitoring and control
- High reproducibility and long-term stability
- Function control and information on-site thanks to LEDs and digital display
- Long-term stable temperature sensor made of platinum (Pt100 class A as per IEC 60751)
- High accuracy across the entire ambient temperature range and short response time
- Operation and visualisation also with PC and FieldCare or ReadWin 2000 configuration software
- DESINA-compliant

from **€192.00**

Price as of 09.12.2022

More information and current pricing:

[www.casc.endress.com/TTR31](http://www.casc.endress.com/TTR31)

### Specs at a glance

- **Accuracy** -50...75 °C: <0,5 K (-58...167 °F: <0,9 °F) 75...150 °C: <0,65 K (167...302 °F: <1,2 °F)
- **Operating temperature range** -50...150 °C (-58...302 °F)

**Field of application:** Cost efficiency, optimal use of space, reliable operation, easy installation and commissioning indicate modern process measuring technology. The temperature switch completely fulfills these requirements. Designed for the safe measurement and monitoring of process temperatures it can be selected between one or two switch outputs as well as one switch output and one standardized analog output. Vibration-proof integrated thin-film sensors guarantee highest operational safety.

### Features and specifications

## Temperature switch

**Measuring principle**

Temperature switch

**Characteristic / Application**

Intelligent temperature switch with Pt100 sensor (Class A)

DESINA compliant

**Auxiliary power supply**

12...30 V DC

**Accuracy**

-50...75 °C: &lt;0,5 K

(-58...167 °F: &lt;0,9 °F)

75...150 °C: &lt;0,65 K

(167...302 °F: &lt;1,2 °F)

**Long term drift**

&lt;0,1K/a (&lt;0,2°F/a)

**Operating temperature range**

-50...150 °C (-58...302 °F)

**Process connection**

threads, clamp connection

**Hint**

Not defined

More information [www.casc.endress.com/TTR31](http://www.casc.endress.com/TTR31)