

Ultrasonic measurement Time-of-Flight Prosonic FDU90

Ultrasonic sensor for level and flow measurement for connection to FMU9x (measuring range up to 3m)



Benefits:

- Integrated temperature sensor for Time-of-Flight correction. Accurate measurements are possible, even if temperature changes are present
- Hermetically welded PVDF sensor for highest chemical resistance
- Suited for rough ambient conditions thanks to separate installation from the transmitter (up to 300m)
- Reduced build-up formation because of the self-cleaning effect
- Integrated automatic sensor detection for transmitters FMU90 / FMU95 for simple commissioning
- Weather resistant and flood-proof (IP 68)
- Integrated heating against a build-up of ice at the sensor (optional) ensures reliable measurement

More information and current pricing:

www.ch.endress.com/FDU90

Specs at a glance

- **Process temperature** -40 °C ... 80 °C (-40 °F ... 176 °F)
- **Process pressure absolute / max. overpressure limit** 0.7 bar ... 4 bar abs (10 psi ... 58 psi)
- **Max. measurement distance** 1.2 m (3.9 ft)
- **Accuracy** +/- 2mm + 0.17% of measured distance
- **Main wetted parts** PVDF (IP68 / NEMA6P)

Field of application: The FDU90 ultrasonic sensor for continuous, non-contact and maintenance-free level measurement of fluids, pastes, sludges and powdery to coarse bulk materials. But also for flow measurement in open channels and measuring weirs. The measurement is unaffected by dielectric constant, density or humidity and also

unaffected by build-up due to the self-cleaning effect of sensors. Suited for explosion hazardous areas. Maximum measuring range in liquids 3m (9.8ft), solids 1.2m (3.9ft).

Features and specifications

Continuous / Solids

Measuring principle

Ultrasonic

Characteristic / Application

Separated version with field housing or top hat rail housing for control cabinet instrumentation, 300m in-between sensor and transmitter

Supply / Communication

4-wire (HART, PROFIBUS DP)

Accuracy

+/- 2mm + 0.17% of measured distance

Ambient temperature

-40 °C ... 80 °C
(-40 °F ... 176 °F)

Process temperature

-40 °C ... 80 °C
(-40 °F ... 176 °F)

Process pressure absolute / max. overpressure limit

0.7 bar ... 4 bar abs
(10 psi ... 58 psi)

Main wetted parts

PVDF (IP68 / NEMA6P)

Continuous / Solids**Process connection**

Front side thread:

G / NPT 1 1/2"

Rear side thread:

G / NPT 1"

Ceiling mounting

Blocking distance

0.07 m (0.23 ft)

Max. measurement distance

1.2 m (3.9 ft)

Communication

Transmitter:

4 ... 20 mA HART

Profibus DP

Certificates / Approvals

ATEX, FM, CSA, IEC Ex, INMETRO, NEPSI, EAC Ex

Options

Second 4...20mA output

Components

Transmitter:

FMU90

Liquids**Measuring principle**

Ultrasonic

Liquids

Product headline

Version with separate transmitter in field housing or top hat rail housing
Cost effective solution for open channel flow measurement in water /
wastewater plants

Max. measurement error

accuracy:

distance measurement: +/- 2mm + 0.17%

resolution:

distance measurement: 1m

Measuring range

max measuring distance up to 3 m / 9.8 ft

Max. process pressure

atm.

Medium temperature range

-40 °C ... 80 °C

(-40 °F ... 176 °F)

Degree of protection

IP68

Display/Operation

Transmitter

Outputs

Transmitter:

4 ... 20 mA HART

PROFIBUS DP

Inputs

Transmitter

Digital communication

HART, PROFIBUS DP

Liquids**Hazardous area approvals**ATEX, FM, CSA, IEC Ex, INMETRO, NEPSI, EAC Ex

Continuous / Liquids**Measuring principle**Ultrasonic

Characteristic / ApplicationSeparated version with field housing or top hat rail housing for control cabinet instrumentation, 300m in-between sensor and transmitter

SpecialitiesFloating protection tube

Supply / Communication4-wire (HART, Profibus DP)

Accuracy+/- 2mm + 0.17% of measured distance

Ambient temperature-40 °C ... 80 °C
(-40 °F ... 176 °F)

Process temperature-40 °C ... 80 °C
(-40 °F ... 176 °F)

Process pressure absolute / max. overpressure limit0.7 bar ... 4 bar abs
(10 psi ... 58 psi)

Main wetted partsPVDF (IP68 / NEMA6P)

Continuous / Liquids**Process connection**

Front side thread:

G / NPT 1 1/2"

Rear side thread:

G / NPT 1"

Ceiling mounting

Blocking distance

0.07 m (0.23 ft)

Application

Application

Max. measurement distance

Max. measurement distance

Communication

Transmitter:

4 ... 20 mA HART

Profibus DP

Certificates / Approvals

ATEX, FM, CSA, IEC Ex, INMETRO, NEPSI, EAC Ex

Options

Second 4...20mA output

Components

Transmitter:

FMU90, FMU95

Continuous / Liquids

Application limits

Foam / high turbulence possible:

FDU91

For tank farms scanner:

FMU95

More information www.ch.endress.com/FDU90