


Ecograph T RSG35

Universal Graphic Data Manager

Paperless recording, visualization and monitoring of the process values at the same time



Edut:

- Versatile: up to 12 universal inputs record a wide range of measuring signals
- Clear layout: 5.7" TFT screen for displaying measured values in a maximum of four groups, with digital, bar graph and curve display
- Safe: reliable data archiving with internal memory and separate SD card
- Easy: intuitive operation via the navigator (jog/shuttle dial) on site, or user-friendly operation at the PC via the integrated web server
- Compact: low installation depth, saves space and money
- System-enabled: common interfaces such as Ethernet, RS232/485, USB and optional slave function for Modbus RTU/TCP
- Informative: e-mail notification in event of alarms and limit violation

alk. **778,00 €**

Hinta 17.10.2021

Lisätietoja ja ajankohtainen hinnasto:

www.fi.endress.com/RSG35

Tärkeimmät tekniset tiedot

- **Input** 12 analog (max) (U, I, TC, RTD, frequency, pulse) 6 digital (max)
- **Output** 6 relays (max) 1 transmitter power supply
- **Display** TFT 5.7" colour graphic display
- **Power supply** 100...230 V AC +/-10% 24V (-10%, +15%) AC/DC
- **Storage/Recording** Internal memory SD card USB flash drive

Käyttöalue: Safe and complete recording and visualization of all process sequences. Demands on process monitoring and data recording are becoming more and more complex. Because every measurement value counts, the Universal Data Manager Ecograph T RSG35 records, visualizes and monitors all analog or digital input signals. The unit is easy to use and comes with features to save costs and simplify data

acquisition. Due to its variety of communication possibilities a simple system integration is possible.

Ominaisuudet ja tiedot

Data Acquisition

Mittausperiaate

Electronic Data Acquisition

Functions

"Secure data recording and signal analysis

Visualization

Integrated web server for device set-up

E-Mail notification

100 ms scan rate

Modular design for simple expansion

Data readout and processing via Field Data Manager

Software

OPC server for indication of instantaneous values (optional)

Maximal input

"12 Analog (U, I, TC, RTD, frequency, pulse)

6 Digital"

Maximal output

6 Relays

1 Transmitter power supply`

Interface

RS232/485 (optional)

Ethernet

USB

Modbus RTU Slave (optional)

Modbus TCP Slave (optional)

Storage/Recording

Internal memory

SD card

USB flash drive

Data Acquisition**Display**TFT 5.7" colour graphic display

HousingPanel
desktop housing
field housing

Power supply100...230 V AC +/-10%
24V (-10%, +15%) AC/DC

CertificationUL
CSA GP

Software packageMathematics

Data Manager & Data Logger**Mittausperiaate**Data manager

Measuring principleUniversal Graphic Data Manager

FunctionSecure data recording made easy - Monitor, visualize, record and communicate process values - every measurement value counts!

Input12 analog (max) (U, I, TC, RTD, frequency, pulse)
6 digital (max)

Output6 relays (max)
1 transmitter power supply

Data Manager & Data Logger

Interface

RS232/485 (optional)
Ethernet
USB
Modbus RTU/TCP Slave (optional)

Storage/Recording

internal memory
SD card
USB flash drive

Display

TFT 5.7" colour graphic display

Housing

panel mounting
desktop housing
field housing

Certificates

UL recognized
CSA

Software package

mathematics

Lisätietoja www.fi.endress.com/RSG35