

## Promass 80P



Več informacij in aktualne cene:

[www.si.endress.com/80P](http://www.si.endress.com/80P)

### Prednosti:

- Highest process quality – fully compliant to industry requirements
- Fewer process measuring points – multivariable measurement (flow, density, temperature)
- Space-saving installation – no in/outlet run needs
- Cost-effective – dedicated design for standard applications
- Safe operation – display provides easy readable process information
- Fully industry compliant – IEC/EN/NAMUR

### Lastnosti na dlani

- **Max. measurement error** Mass flow (liquid):  $\pm 0.15\%$  Volume flow (liquid):  $\pm 0.15\%$  Mass flow (gas):  $\pm 0.5\%$  Density (liquid):  $\pm 0.0005 \text{ g/cm}^3$
- **Measuring range** 0 to 70 000 kg/h (0 to 2570 lb/min)
- **Medium temperature range**  $-50$  to  $+200 \text{ }^\circ\text{C}$  ( $-58$  to  $+392 \text{ }^\circ\text{F}$ )
- **Max. process pressure** PN 63, Class 300, 40K
- **Wetted materials** Measuring tube: 1.4435 (316L) Connection: 1.4435 (316L); 1.4404 (316/316L)

**Področje uporabe:** Promass P offers the enhanced performance of a bent tube meter and the drainability of a straight tube meter without any compromise, between accuracy and drainability. Combined with the proven Promass 80 transmitter with push buttons, Promass 80P offers a cost effective solution for applications in sterile environments in the life sciences industry.

### Lastnosti in specifikacije

Density

**Merilni princip**

Coriolis

## Density

**Characteristic / Application**

Coriolis mass flowmeter complying with ASME BPE, ISPE, FDA, 3-A

**Ambient temperature**

-20...+65°C  
(-4...+140°F)

**Process temperature**

-50...+200°C  
(-58...+392°F)

**Process pressure absolute**

PN 16...40  
CI 150...300  
JIS 20...40K

**Wetted parts**

316L/1.4435

**Output**

4...20mA  
Pulse/Frequency  
Status

**Certificates / Approvals**

ATEX  
FM  
CSA IECEx TIIS NEPSI

## Density/Concentration

**Merilni princip**

Coriolis

**Product headline**

The specialist for life sciences with a compact or remote transmitter. Dedicated for applications under sterile conditions in the life sciences industry.

---

## Density/Concentration

---

### Sensor features

Highest process quality – fully compliant to industry requirements. Fewer process measuring points – multivariable measurement (flow, density, temperature). Space - saving installation – no in/outlet run needs. ASME BPE, 3-A and EHEDG conform & low delta ferrite. Electropolished measuring tube in 1.4435 (316L).

---

### Transmitter features

Cost - effective – dedicated design for standard applications. Safe operation – display provides easy readable process information. Fully industry compliant – IEC/EN/NAMUR. 2 - line backlit display with push buttons. Device in compact or remote version.

---

### Nominal diameter range

DN 8 to 50 ( $\frac{3}{8}$  to 2")

---

### Wetted materials

Measuring tube: 1.4435 (316L)

Connection: 1.4435 (316L); 1.4404 (316/316L)

---

### Measured variables

Mass flow, density, temperature, volume flow, corrected volume flow, reference density

---

### Max. measurement error

Mass flow (liquid):  $\pm 0.15$  %

Volume flow (liquid):  $\pm 0.15$  %

Mass flow (gas):  $\pm 0.5$  %

Density (liquid):  $\pm 0.0005$  g/cm<sup>3</sup>

---

### Measuring range

0 to 70 000 kg/h (0 to 2570 lb/min)

---

### Max. process pressure

PN 63, Class 300, 40K

---

### Medium temperature range

-50 to +200 °C (-58 to +392 °F)

---

---

**Density/Concentration****Ambient temperature range**

Standard: -20 to +60 °C (-4 to +140 °F)

Option: -40 to +60 °C (-40 to +140 °F)

---

**Sensor housing material**1.4301 (304), corrosion resistant

---

**Transmitter housing material**

Powder - coated die - cast aluminium

1.4301 (304), sheet

CF3M (316L), cast

---

**Degree of protection**IP67, type 4X enclosure. Remote transmitter: IP67, type 4X enclosure

---

**Display/Operation**

2 - line backlit display with push buttons

Configuration via local display and operating tools possible

---

**Outputs**

3 outputs:

0 - 20 mA (active)/4 - 20 mA (active/passive)

Pulse/frequency/switch output (passive)

---

**Inputs**Status input

---

**Digital communication**

HART

PROFIBUS PA

---

**Power supply**

DC 16 to 62 V

AC 85 to 260 V (45 to 65 Hz)

AC 20 to 55 V (45 to 65 Hz)

---

**Hazardous area approvals**ATEX, IECEx, FM, CSA, NEPSI

---

---

**Density/Concentration****Product safety**

CE, C-tick, EAC marking

---

**Functional safety**

Functional safety according to IEC 61508, applicable in safety-relevant applications in accordance with IEC 61511

---

**Metrological approvals and certificates**

Calibration performed on accredited calibration facilities (acc. to ISO/IEC 17025), NAMUR

---

**Pressure approvals and certificates**

PED, CRN

---

**Material certificates**

3.1 material

---

**Hygienic approvals and certificates**

3-A, FDA, ASME BPE, ISPE

---

**Gas****Merilni princip**

Coriolis

---

**Product headline**

The specialist for life sciences with a compact or remote transmitter. Dedicated for applications under sterile conditions in the life sciences industry.

---

**Sensor features**

Highest process quality – fully compliant to industry requirements. Fewer process measuring points – multivariable measurement (flow, density, temperature). Space - saving installation – no in/outlet run needs. ASME BPE, 3-A and EHEDG conform & low delta ferrite. Electropolished measuring tube in 1.4435 (316L).

---

## Gas

**Transmitter features**

Cost - effective – dedicated design for standard applications. Safe operation – display provides easy readable process information. Fully industry compliant – IEC/EN/NAMUR. 2 - line backlit display with push buttons. Device in compact or remote version.

**Nominal diameter range**

DN 8 to 50 ( $\frac{3}{8}$  to 2")

**Wetted materials**

Measuring tube: 1.4435 (316L)

Connection: 1.4435 (316L); 1.4404 (316/316L)

**Measured variables**

Mass flow, density, temperature, volume flow, corrected volume flow, reference density

**Max. measurement error**

Mass flow (liquid):  $\pm 0.15$  %

Volume flow (liquid):  $\pm 0.15$  %

Mass flow (gas):  $\pm 0.5$  %

Density (liquid):  $\pm 0.0005$  g/cm<sup>3</sup>

**Measuring range**

0 to 70 000 kg/h (0 to 2570 lb/min)

**Max. process pressure**

PN 63, Class 300, 40K

**Medium temperature range**

-50 to +200 °C (-58 to +392 °F)

**Ambient temperature range**

Standard: -20 to +60 °C (-4 to +140 °F)

Option: -40 to +60 °C (-40 to +140 °F)

**Sensor housing material**

1.4301 (304), corrosion resistant

## Gas

**Transmitter housing material**

Powder - coated die - cast aluminium  
1.4301 (304), sheet  
CF3M (316L), cast

---

**Degree of protection**

IP67, type 4X enclosure. Remote transmitter: IP67, type 4X enclosure

---

**Display/Operation**

2 - line backlit display with push buttons  
Configuration via local display and operating tools possible

---

**Outputs**

3 outputs:  
0 - 20 mA (active)/4 - 20 mA (active/passive)  
Pulse/frequency/switch output (passive)

---

**Inputs**

Status input

---

**Digital communication**

HART  
PROFIBUS PA

---

**Power supply**

DC 16 to 62 V  
AC 85 to 260 V (45 to 65 Hz)  
AC 20 to 55 V (45 to 65 Hz)

---

**Hazardous area approvals**

ATEX, IECEX, FM, CSA, NEPSI

---

**Other approvals and certificates**

3.1 material, calibration performed on accredited calibration facilities  
(acc. to ISO/IEC 17025), NAMUR, SIL  
PED, CRN  
3-A, FDA, ASME BPE, ISPE

---

---

**Gas****Product safety**

CE, C-tick, EAC marking

---

**Functional safety**

Functional safety according to IEC 61508, applicable in safety-relevant applications in accordance with IEC 61511

---

**Metrological approvals and certificates**

Calibration performed on accredited calibration facilities (acc. to ISO/IEC 17025), NAMUR

---

**Pressure approvals and certificates**

PED, CRN

---

**Material certificates**

3.1 material

---

**Hygienic approvals and certificates**

3-A, FDA, ASME BPE, ISPE

---

**Liquids****Merilni princip**

Coriolis

---

**Product headline**

The specialist for life sciences with a compact or remote transmitter. Dedicated for applications under sterile conditions in the life sciences industry.

---

**Sensor features**

Highest process quality – fully compliant to industry requirements. Fewer process measuring points – multivariable measurement (flow, density, temperature). Space - saving installation – no in/outlet run needs. ASME BPE, 3-A and EHEDG conform & low delta ferrite. Electropolished measuring tube in 1.4435 (316L).

---



## Liquids

### Transmitter features

Cost - effective – dedicated design for standard applications. Safe operation – display provides easy readable process information. Fully industry compliant – IEC/EN/NAMUR. 2 - line backlit display with push buttons. Device in compact or remote version.

---

### Nominal diameter range

DN 8 to 50 ( $\frac{3}{8}$  to 2")

---

### Wetted materials

Measuring tube: 1.4435 (316L)

Connection: 1.4435 (316L); 1.4404 (316/316L)

---

### Measured variables

Mass flow, density, temperature, volume flow, corrected volume flow, reference density

---

### Max. measurement error

Mass flow (liquid):  $\pm 0.15$  %

Volume flow (liquid):  $\pm 0.15$  %

Mass flow (gas):  $\pm 0.5$  %

Density (liquid):  $\pm 0.0005$  g/cm<sup>3</sup>

---

### Measuring range

0 to 70 000 kg/h (0 to 2570 lb/min)

---

### Max. process pressure

PN 63, Class 300, 40K

---

### Medium temperature range

-50 to +200 °C (-58 to +392 °F)

---

### Ambient temperature range

Standard: -20 to +60 °C (-4 to +140 °F)

Option: -40 to +60 °C (-40 to +140 °F)

---

### Sensor housing material

1.4301 (304), corrosion resistant

---

---

## Liquids

### **Transmitter housing material**

Powder - coated die - cast aluminium  
1.4301 (304), sheet  
CF3M (316L), cast

---

### **Degree of protection**

IP67, type 4X enclosure. Remote transmitter: IP67, type 4X enclosure

---

### **Display/Operation**

2 - line backlit display with push buttons  
Configuration via local display and operating tools possible

---

### **Outputs**

3 outputs:  
0 - 20 mA (active)/4 - 20 mA (active/passive)  
Pulse/frequency/switch output (passive)

---

### **Inputs**

Status input

---

### **Digital communication**

HART  
PROFIBUS PA

---

### **Power supply**

DC 16 to 62 V  
AC 85 to 260 V (45 to 65 Hz)  
AC 20 to 55 V (45 to 65 Hz)

---

### **Hazardous area approvals**

ATEX, IECEx, FM, CSA, NEPSI

---

### **Other approvals and certificates**

3.1 material, calibration performed on accredited calibration facilities  
(acc. to ISO/IEC 17025), NAMUR, SIL  
PED, CRN  
3-A, FDA, ASME BPE, ISPE

---

## Liquids

### **Product safety**

CE, C-tick, EAC marking

---

### **Functional safety**

Functional safety according to IEC 61508, applicable in safety-relevant applications in accordance with IEC 61511

---

### **Metrological approvals and certificates**

Calibration performed on accredited calibration facilities (acc. to ISO/IEC 17025), NAMUR

---

### **Pressure approvals and certificates**

PED, CRN

---

### **Material certificates**

3.1 material

---

### **Hygienic approvals and certificates**

3-A, FDA, ASME BPE, ISPE

---

Več informacij [www.si.endress.com/80P](http://www.si.endress.com/80P)