

## Promass 80F



More information and current pricing:

[www.th.endress.com/80F](http://www.th.endress.com/80F)

### Benefits:

- Highest process safety – immune to fluctuating and harsh environments
- Fewer process measuring points – multivariable measurement (flow, density, temperature)
- Space-saving installation – no in/outlet run needs
- Cost-effective – dedicated design for standard applications
- Safe operation – display provides easy readable process information
- Fully industry compliant – IEC/EN/NAMUR

### Specs at a glance

- **Max. measurement error** Mass flow (liquid):  $\pm 0.15\%$  (standard),  $0.1\%$  (option) Volume flow (liquid):  $\pm 0.15\%$  Mass flow (gas):  $\pm 0.35\%$  Density (liquid):  $\pm 0.0005 \text{ g/cm}^3$
- **Measuring range** 0 to 2 200 000 kg/h (0 to 80 840 lb/min)
- **Medium temperature range** Standard:  $-50$  to  $+200 \text{ }^\circ\text{C}$  ( $-58$  to  $+392 \text{ }^\circ\text{F}$ ) High temperature:  $-50$  to  $+350 \text{ }^\circ\text{C}$  ( $-58$  to  $+662 \text{ }^\circ\text{F}$ )
- **Max. process pressure** PN 100, Class 600, 63K
- **Wetted materials** Measuring tube: 1.4539 (904L); 1.4404 (316/316L); Alloy C22, 2.4602 (UNS N06022) Connection: 1.4404 (316/316L); Alloy C22, 2.4602 (UNS N06022)

**Field of application:** Promass F has a long standing reputation as a highly accurate and robust device. It is suited for a broadest range of applications. Combined with the proven Promass 80 transmitter with push buttons, Promass 80F offers highest measurement performance for liquids and gases under varying, demanding process conditions.

### Features and specifications

Liquids

Measuring principle

Coriolis

---

## Liquids

---

### Product headline

The robust flowmeter for demanding applications with a compact or remote transmitter. Highest measurement performance for liquids and gases under varying, demanding process conditions.

---

### Sensor features

Highest process safety – immune to fluctuating and harsh environments. Fewer process measuring points – multivariable measurement (flow, density, temperature). Space - saving installation – no in/outlet run needs. Mass flow: measurement error  $\pm 0,05$  % (PremiumCal). pressure-rated sensor housing up to 40 bar (580 psi).

---

### Transmitter features

Cost - effective – dedicated design for standard applications. Safe operation – display provides easy readable process information. Fully industry compliant – IEC/EN/NAMUR. 2 - line backlit display with push buttons. Device in compact or remote version.

---

### Nominal diameter range

DN 8 to 250 ( $\frac{3}{8}$  to 10")

High temperature: DN 25 (1"), DN 50 (2"), DN 80 (3")

---

### Wetted materials

Measuring tube: 1.4539 (904L); 1.4404 (316/316L); Alloy C22, 2.4602 (UNS N06022)

Connection: 1.4404 (316/316L); Alloy C22, 2.4602 (UNS N06022)

---

### Measured variables

Mass flow, density, temperature, volume flow, corrected volume flow, reference density

---

### Max. measurement error

Mass flow (liquid):  $\pm 0.15$  % (standard), 0.1 % (option)

Volume flow (liquid):  $\pm 0.15$  %

Mass flow (gas):  $\pm 0.35$  %

Density (liquid):  $\pm 0.0005$  g/cm<sup>3</sup>

---

---

## Liquids

**Measuring range**

0 to 2 200 000 kg/h (0 to 80 840 lb/min)

---

**Max. process pressure**

PN 100, Class 600, 63K

---

**Medium temperature range**

Standard: -50 to +200 °C (-58 to +392 °F)

High temperature: -50 to +350 °C (-58 to +662 °F)

---

**Ambient temperature range**

Standard: -20 to +60 °C (-4 to +140 °F)

Option: -40 to +60 °C (-40 to +140 °F)

---

**Sensor housing material**

1.4301/1.4307 (304L), corrosion resistant

---

**Transmitter housing material**

Powder - coated die - cast aluminium

1.4301 (304), sheet

CF3M (316L), cast

---

**Degree of protection**

IP67, type 4X enclosure. Remote transmitter: IP67, type 4X enclosure

---

**Display/Operation**

2 - line backlit display with push buttons

Configuration via local display and operating tools possible

---

**Outputs**

3 outputs:

0 - 20 mA (active)/4 - 20 mA (active/passive)

Pulse/frequency/switch output (passive)

---

**Inputs**

Status input

---

## Liquids

### Digital communication

HART  
PROFIBUS PA

---

### Power supply

DC 16 to 62 V  
AC 85 to 260 V (45 to 65 Hz)  
AC 20 to 55 V (45 to 65 Hz)

---

### Hazardous area approvals

ATEX, IECEx, FM, CSA, NEPSI

---

### Other approvals and certificates

3.1 material, calibration performed on accredited calibration facilities (acc. to ISO/IEC 17025), NAMUR, SIL, marine  
PED, CRN, AD 2000  
3-A, FDA  
NACE MR0175/MR0103, PMI; welding test acc. to EN, ASME, NORSOK

---

### Product safety

CE, C-tick, EAC marking

---

### Functional safety

Functional safety according to IEC 61508, applicable in safety-relevant applications in accordance with IEC 61511

---

### Metrological approvals and certificates

Calibration performed on accredited calibration facilities (acc. to ISO/IEC 17025), NAMUR

---

### Marine approvals and certificates

Marine approval

---

### Pressure approvals and certificates

PED, CRN, AD 2000

---

### Material certificates

3.1 material  
NACE MR0175/MR0103, PMI; welding test acc. to EN, ASME, NORSOK

---

## Liquids

### Hygienic approvals and certificates

3-A, EHEDG, FDA

---

## Gas

### Measuring principle

Coriolis

---

### Product headline

The robust flowmeter for demanding applications with a compact or remote transmitter. Highest measurement performance for liquids and gases under varying, demanding process conditions.

---

### Sensor features

Highest process safety – immune to fluctuating and harsh environments. Fewer process measuring points – multivariable measurement (flow, density, temperature). Space - saving installation – no in/outlet run needs. Mass flow: measurement error  $\pm 0,05$  % (PremiumCal). pressure-rated sensor housing up to 40 bar (580 psi).

---

### Transmitter features

Cost - effective – dedicated design for standard applications. Safe operation – display provides easy readable process information. Fully industry compliant – IEC/EN/NAMUR. 2 - line backlit display with push buttons. Device in compact or remote version.

---

### Nominal diameter range

DN 8 to 250 ( $\frac{3}{8}$  to 10")

High temperature: DN 25 (1"), DN 50 (2"), DN 80 (3")

---

### Wetted materials

Measuring tube: 1.4539 (904L); 1.4404 (316/316L); Alloy C22, 2.4602 (UNS N06022)

Connection: 1.4404 (316/316L); Alloy C22, 2.4602 (UNS N06022)

---

### Measured variables

Mass flow, density, temperature, volume flow, corrected volume flow, reference density

---

## Gas

**Max. measurement error**

Mass flow (liquid):  $\pm 0.15$  % (standard), 0.1 % (option)

Volume flow (liquid):  $\pm 0.15$  %

Mass flow (gas):  $\pm 0.35$  %

Density (liquid):  $\pm 0.0005$  g/cm<sup>3</sup>

---

**Measuring range**

0 to 2 200 000 kg/h (0 to 80 840 lb/min)

---

**Max. process pressure**

PN 100, Class 600, 63K

---

**Medium temperature range**

Standard:  $-50$  to  $+200$  °C ( $-58$  to  $+392$  °F)

High temperature:  $-50$  to  $+350$  °C ( $-58$  to  $+662$  °F)

---

**Ambient temperature range**

Standard:  $-20$  to  $+60$  °C ( $-4$  to  $+140$  °F)

Option:  $-40$  to  $+60$  °C ( $-40$  to  $+140$  °F)

---

**Sensor housing material**

1.4301/1.4307 (304L), corrosion resistant

---

**Transmitter housing material**

Powder - coated die - cast aluminium

1.4301 (304), sheet

CF3M (316L), cast

---

**Degree of protection**

IP67, type 4X enclosure. Remote transmitter: IP67, type 4X enclosure

---

**Display/Operation**

2 - line backlit display with push buttons

Configuration via local display and operating tools possible

---

**Outputs**

3 outputs:

0 - 20 mA (active)/4 - 20 mA (active/passive)

Pulse/frequency/switch output (passive)

---

## Gas

**Inputs**

Status input

**Digital communication**

HART

PROFIBUS PA

**Power supply**

DC 16 to 62 V

AC 85 to 260 V (45 to 65 Hz)

AC 20 to 55 V (45 to 65 Hz)

**Hazardous area approvals**

ATEX, IECEx, FM, CSA, NEPSI

**Other approvals and certificates**

3.1 material, calibration performed on accredited calibration facilities (acc. to ISO/IEC 17025), NAMUR, SIL, marine

PED, CRN, AD 2000

3-A,, FDA

NACE MR0175/MR0103, PMI; welding test acc. to EN, ASME, NORSOK

**Product safety**

CE, C-tick, EAC marking

**Functional safety**

Functional safety according to IEC 61508, applicable in safety-relevant applications in accordance with IEC 61511

**Metrological approvals and certificates**

Calibration performed on accredited calibration facilities (acc. to ISO/IEC 17025), NAMUR

**Marine approvals and certificates**

Marine approval

**Pressure approvals and certificates**

PED, CRN, AD 2000

---

**Gas****Material certificates**

3.1 material

NACE MR0175/MR0103, PMI; welding test acc. to EN, ASME, NORSOK

---

**Hygienic approvals and certificates**3-A, EHEDG, FDA

---

**Steam****Measuring principle**Coriolis

---

**Product headline**

The robust flowmeter for demanding applications with a compact or remote transmitter. Highest measurement performance for liquids and gases under varying, demanding process conditions.

---

**Sensor features**

Highest process safety – immune to fluctuating and harsh environments. Fewer process measuring points – multivariable measurement (flow, density, temperature). Space - saving installation – no in/outlet run needs. Mass flow: measurement error  $\pm 0,05$  % (PremiumCal). pressure-rated sensor housing up to 40 bar (580 psi).

---

**Transmitter features**

Cost - effective – dedicated design for standard applications. Safe operation – display provides easy readable process information. Fully industry compliant – IEC/EN/NAMUR. 2 - line backlit display with push buttons. Device in compact or remote version.

---

**Nominal diameter range**DN 8 to 250 ( $\frac{3}{8}$  to 10")High temperature: DN 25 (1"), DN 50 (2"), DN 80 (3")

---

**Wetted materials**

Measuring tube: 1.4539 (904L); 1.4404 (316/316L); Alloy C22, 2.4602 (UNS N06022)

Connection: 1.4404 (316/316L); Alloy C22, 2.4602 (UNS N06022)

---



---

**Steam****Measured variables**

Mass flow, density, temperature, volume flow, corrected volume flow, reference density

---

**Max. measurement error**

Mass flow (liquid):  $\pm 0.15$  % (standard), 0.1 % (option)

Volume flow (liquid):  $\pm 0.15$  %

Mass flow (gas):  $\pm 0.35$  %

Density (liquid):  $\pm 0.0005$  g/cm<sup>3</sup>

---

**Measuring range**

0 to 2 200 000 kg/h (0 to 80 840 lb/min)

---

**Max. process pressure**

PN 100, Class 600, 63K

---

**Medium temperature range**

Standard:  $-50$  to  $+200$  °C ( $-58$  to  $+392$  °F)

High temperature:  $-50$  to  $+350$  °C ( $-58$  to  $+662$  °F)

---

**Ambient temperature range**

Standard:  $-20$  to  $+60$  °C ( $-4$  to  $+140$  °F)

Option:  $-40$  to  $+60$  °C ( $-40$  to  $+140$  °F)

---

**Sensor housing material**

1.4301/1.4307 (304L), corrosion resistant

---

**Transmitter housing material**

Powder - coated die - cast aluminium

1.4301 (304), sheet

CF3M (316L), cast

---

**Degree of protection**

IP67, type 4X enclosure. Remote transmitter: IP67, type 4X enclosure

---

**Display/Operation**

2 - line backlit display with push buttons

Configuration via local display and operating tools possible

---

---

**Steam****Outputs**

3 outputs:

0 - 20 mA (active)/4 - 20 mA (active/passive)

Pulse/frequency/switch output (passive)

---

**Inputs**

Status input

---

**Digital communication**

HART

PROFIBUS PA

---

**Power supply**

DC 16 to 62 V

AC 85 to 260 V (45 to 65 Hz)

AC 20 to 55 V (45 to 65 Hz)

---

**Hazardous area approvals**

ATEX, IECEx, FM, CSA, NEPSI

---

**Other approvals and certificates**

3.1 material, calibration performed on accredited calibration facilities (acc. to ISO/IEC 17025), NAMUR, SIL, marine

PED, CRN, AD 2000

3-A, FDA

NACE MR0175/MR0103, PMI; welding test acc. to EN, ASME, NORSOK

---

**Product safety**

CE, C-tick, EAC marking

---

**Functional safety**

Functional safety according to IEC 61508, applicable in safety-relevant applications in accordance with IEC 61511

---

**Metrological approvals and certificates**

Calibration performed on accredited calibration facilities (acc. to ISO/IEC 17025), NAMUR

---

## Steam

**Marine approvals and certificates**

Marine approval

**Pressure approvals and certificates**

PED, CRN, AD 2000

**Material certificates**

3.1 material

NACE MR0175/MR0103, PMI; welding test acc. to EN, ASME, NORSOK

**Hygienic approvals and certificates**

3-A, EHEDG, FDA

## Density

**Measuring principle**

Coriolis

**Characteristic / Application**

The universal and multivariable flowmeter for liquids and gases

**Ambient temperature**

-20...+65°C

(-4...+140°F)

**Process temperature**

-50...+350°C

(-58...+662°F)

**Process pressure**

PN 16...100

Cl 150...600

JIS 10...63K

**Wetted parts**

904L/1.4539

Alloy C-22

---

## Density

### Output

4...20mA  
Pulse/Frequency  
Status

---

### Certificates / Approvals

ATEX  
FM  
CSA  
TIIS

---

## Density/Concentration

### Measuring principle

Coriolis

---

### Product headline

The robust flowmeter for demanding applications with a compact or remote transmitter. Highest measurement performance for liquids and gases under varying, demanding process conditions.

---

### Sensor features

Highest process safety – immune to fluctuating and harsh environments. Fewer process measuring points – multivariable measurement (flow, density, temperature). Space - saving installation – no in/outlet run needs. Mass flow: measurement error  $\pm 0,05$  % (PremiumCal). pressure-rated sensor housing up to 40 bar (580 psi).

---

### Transmitter features

Cost - effective – dedicated design for standard applications. Safe operation – display provides easy readable process information. Fully industry compliant – IEC/EN/NAMUR. 2 - line backlit display with push buttons. Device in compact or remote version.

---

### Nominal diameter range

DN 8 to 250 ( $\frac{3}{8}$  to 10")  
High temperature: DN 25 (1"), DN 50 (2"), DN 80 (3")

---

---

**Density/Concentration****Wetted materials**

Measuring tube: 1.4539 (904L); 1.4404 (316/316L); Alloy C22, 2.4602 (UNS N06022)

Connection: 1.4404 (316/316L); Alloy C22, 2.4602 (UNS N06022)

---

**Measured variables**

Mass flow, density, temperature, volume flow, corrected volume flow, reference density

---

**Max. measurement error**

Mass flow (liquid):  $\pm 0.15$  % (standard), 0.1 % (option)

Volume flow (liquid):  $\pm 0.15$  %

Mass flow (gas):  $\pm 0.35$  %

Density (liquid):  $\pm 0.0005$  g/cm<sup>3</sup>

---

**Measuring range**

0 to 2 200 000 kg/h (0 to 80 840 lb/min)

---

**Max. process pressure**

PN 100, Class 600, 63K

---

**Medium temperature range**

Standard:  $-50$  to  $+200$  °C ( $-58$  to  $+392$  °F)

High temperature:  $-50$  to  $+350$  °C ( $-58$  to  $+662$  °F)

---

**Ambient temperature range**

Standard:  $-20$  to  $+60$  °C ( $-4$  to  $+140$  °F)

Option:  $-40$  to  $+60$  °C ( $-40$  to  $+140$  °F)

---

**Sensor housing material**

1.4301/1.4307 (304L), corrosion resistant

---

**Transmitter housing material**

Powder - coated die - cast aluminium

1.4301 (304), sheet

CF3M (316L), cast

---

**Degree of protection**

IP67, type 4X enclosure. Remote transmitter: IP67, type 4X enclosure

---

---

## Density/Concentration

---

### Display/Operation

2 - line backlit display with push buttons  
Configuration via local display and operating tools possible

---

### Outputs

3 outputs:  
0 - 20 mA (active)/4 - 20 mA (active/passive)  
Pulse/frequency/switch output (passive)

---

### Inputs

Status input

---

### Digital communication

HART  
PROFIBUS PA

---

### Power supply

DC 16 to 62 V  
AC 85 to 260 V (45 to 65 Hz)  
AC 20 to 55 V (45 to 65 Hz)

---

### Hazardous area approvals

ATEX, IECEX, FM, CSA, NEPSI

---

### Product safety

CE, C-tick, EAC marking

---

### Functional safety

Functional safety according to IEC 61508, applicable in safety-relevant applications in accordance with IEC 61511

---

### Metrological approvals and certificates

Calibration performed on accredited calibration facilities (acc. to ISO/IEC 17025), NAMUR

---

### Marine approvals and certificates

Marine approval

---

Density/Concentration

**Pressure approvals and certificates**

PED, CRN, AD 2000

---

**Material certificates**

3.1 material

NACE MR0175/MR0103, PMI; welding test acc. to EN, ASME, NORSOK

---

**Hygienic approvals and certificates**

3-A, EHEDG, FDA

---

More information [www.th.endress.com/80F](http://www.th.endress.com/80F)