

iTEMP TMT72

Temperature transmitter

Transformation of sensor signals into stable and standardized output signals for all industries



More information and current pricing:

www.uk.endress.com/TMT72

Benefits:

- Safe operation in hazardous areas thanks to international approvals
- Reliable operation thanks to sensor and device monitoring
- Integrated Bluetooth® interface for the wireless display of measured values and configuration via E+H SmartBlue (app), optional
- Diagnostics information according to NAMUR NE 107
- Available with plug-on display TID10
- Optimization of the measurement accuracy by sensor-transmitter matching.

Specs at a glance

- **Accuracy** (Pt100, -50...200 °C) ≤ 0,1 K (Pt100, -58...392 °F) ≤ 0,18 °F

Field of application: Unsurpassed reliability, accuracy and long-term stability in critical processes across all industries. The configurable transmitter transfers converted signals from RTD and thermocouple (TC) temperature probes, as well as resistance and voltage signals using HART® communication. Diagnostics information according to NAMUR NE 107. Seamless integration into all major control and asset management systems. Integrated Bluetooth® interface for remote operation via Endress+Hauser SmartBlue App.

Features and specifications

Temperature transmitters**Measuring principle**Head transmitter

Input1 x RTD, TC, Ohm, mV

Output1 x analog 4...20 mA

Auxiliary power supply

10...36 V DC (Head transmitter)

11...36 V DC (DIN rail device)

10/11...30 V DC (Ex-version)

Communication

HART-protocol

Bluetooth® wireless technology

InstallationTerminal head form B / DIN rail / in field

Accuracy(Pt100, -50...200 °C) $\leq 0,1$ K(Pt100, -58...392 °F) $\leq 0,18$ °F

Galvanic isolationyes

Temperature transmitters

Certification

ATEX II1G Ex ia IIC T6

ATEX II3G Ex ic IIC T6 Gc

ATEX II3D Ex tc IIIC Dc

ATEX II3G Ex nA IIC T6

ATEX IECEx II1G Ex ia IIC T6, II2D Ex ia IIIC

ATEX II3G Ex nA IIC T6, II3D

ATEX II2G Ex db IIC T6 Gb, II2D Ex tb IIIC
Db

CSA C/US General Purpose

CSA C/US IS, NI I/1+2/A-D

CSA C/US XP, DIP I, II, III/1+2/A-G

EAC Ex ia IIC T6 Ga

EAC Ex d IIC T6 Gb

IECEX Ex d T6 Gb, Ex tb IIIC Db

INMETRO Ex ia IIC T6 Ga

INMETRO Ex d T6 Gb, Ex tb IIIC Db

INMETRO Ex nA IIC T6 Gc

NEPSI Ex ia IIC T6 Ga

NEPSI Ex d IIC T6 Gb

NEPSI Ex nA II T6 Gc

Temperature transmitters

More information www.uk.endress.com/TMT72